Safety Data Sheet



80% ALCOHOL LIQUID HAND SANITIZER

1. Identification	on			
Product identifier	80% ALCOHOL LIQUID HAND SANITIZ	ER		
Product code	FLSANIH80350ML, FLSANIH80500ML, FLSANIH803.78L, FLSANIH8020L, FLSANIH80208L, FLSANIH801000L			
Other means of identification	None.			
Recommended use of the chemical and restrictions on use	Hand sanitizer.			
Manufacturer	Walter Surface Technologies Inc. 5977, autoroute Transcanadienne Pointe-Claire, QC Canada H9R 1C1 General Information: 1-888-592-5837 info@walter.com www.walter.com	Distributor	Walter Surface Technologies Inc. 810 Day Hill Road Windsor, CT 06095 United States General Information: 1-866-592-5837 info.us@walter.com www.walter.com	
Emergency phone number	INFOTRAC®: 1-800-535-5053 International call collect: 1-352-323-3500 24 hours/day, 7 days/week	1		

2. Hazard identification

Summary

Flammable liquid. Keep away from heat, sparks and open flame. Avoid contact with eyes. Do not breathe vapors. Do not ingest. If medical advice is needed, have this SDS or label at hand.

WHMIS 2015/GHS/OSHA HCS 2012



Flammable liquids (Category 2) Serious eye damage/eye irritation (Category 2B)

DANGER

- H225: Highly flammable liquid and vapour
- H320: Causes eye irritation
- P210: Keep away from heat, sparks, open flames and other ignition sources. No smoking.
- P240: Ground or bond container and receiving equipment.
- P241: Use explosion-proof electrical equipment.
- P242: Use only non-sparking tools.
- P243: Take precautionary measures against static discharge.
- P305+351+338: IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
- P337+313: If eye irritation persists: Get medical advice or attention.

P403+P235+P233: Store in a well-ventilated place. Keep container tightly closed. Keep cool. P501: Dispose of contents and container to a licensed chemical disposal agency in accordance with local, regional and national regulations.

3. Composition/information on ingredients				
Common name	CAS	Weight % content		
Ethyl alcohol	64-17-5	80 %		
Glycerol	56-81-5	1 - 5 %		
- Hydrogen peroxide 7722-84-1 0.1 - 1 %				
Note: The manufacturer withholds the actual concentration range of the ingredients as a trade secret.				

4. First-aid	4. First-aid measures			
Inhalation	Move person to fresh air. If a problem develops or persists, seek medical attention.			
Skin contact	No first aid is necessary in normal use. In case of a spill, flush with water. Remove contaminated clothing and wash before reuse. If a problem develops or persists, seek medical attention.			
Eye contact	Flush with water for at least 15 minutes. Remove contact lenses if easy to do. Hold eyelids apart to rinse properly. If a problem develops or persists, seek medical attention.			
Ingestion	DO NOT induce vomiting, unless recommended by medical personnel. Never give anything by mouth if victim is unconscious or convulsing. If victim is conscious wash out mouth with water and give 1-2 glasses of water to drink. If a problem develops or persists, seek medical attention or contact a Poison Centre.			
Other	No additional information.			
Symptoms	May cause redness, tearing, and eye irritation.			
Notes to the physician	No additional information.			

5. Fire-fighting measures			
	Dry chemicals, water fog, alcohol resistant foam, carbon dioxide (CO2). Do not use a heavy water jet.		
	Highly flammable liquid and vapour. May be ignited by heat, sparks, flame or static electricity. Vapours are heavier than air and may travel to an ignition source distant from the material handling point.		
	Firefighters must wear self contained breathing apparatus with full face mask. Firefighting suit may not be efficient against chemicals.		
actions for fire-fighters	Use water spray to cool fire-exposed containers. Water may be ineffective to extinguish a fire, because mixtures of alcohol and water are also flammable. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply.		

6. Accidental release measures			
Personal precautions, protective equipment and emergency procedures	In the event of a large spill, wear nitrile or neoprene gloves. Wear chemical splash goggles.		
Environmental precautions	Prevent entry into sewers, closed areas and release to the environment.		
Methods and materials for containment and cleaning up	Ventilate the area well. Remove sources of ignition. Absorb with inert material (soil, sand, vermiculite) or wipe up with a damp mop and place in an appropriate waste disposal clearly identified. Finish cleaning by rinsing with water contaminated surface. Never return the spilled product into its original container for reuse.		

7. Handling and	storage
Precautions for safe handling	Keep away from heat, sparks and open flame. Use non-sparking and antistatic tools. Ground/bond all containers when transfering large quantities (5 gallons US or 20 L and more). Use in well ventilated area. Avoid contact with eyes. Do not breathe vapors. Wear eye protection and other protective clothing that are adapted to the task being performed and the risks involved. Keep containers tightly closed when not in use. Do not eat, do not drink and do not smoke during use. Remove contaminated clothing and shoes and wash before reuse.
Conditions for safe storage, including any incompatibilities	Storage and handling should follow the NFPA 30 Flammable and/or Combustible Liquids Code. Ground or bond large containers. Store tightly closed and in properly labelled containers in a cool, dry and well ventilated place. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store away from oxidizing materials and incompatible materials (see section 10). Keep away from direct sunlight and heat.
Storage temperature	<30°C (86°F)

ntrols/pers	onal protection			
Ethyl alcohol: 3	300 ppm.			
STEL		1000 ppm		ACGIH
TWA (8h)		1000 ppm	1880 mg/m ³	RSST
		1000 ppm	1900 mg/m ³	OSHA
TWA (8h)	Inhalable Fraction		5 mg/m³	OSHA
	Mist		10 mg/m ³	ACGIH, RSST
	Mist		15 mg/m³	OSHA
TWA (8h)		1 ppm		ACGIH
		1 ppm	1.4 mg/m ³	OSHA , RSST
limits.	or vapours, mists, aeros	Sols of dust below	w their respective	
In the workplace, wear safety glasses with side shields. If there is a risk of contact with eyes,				
No protective equipment is needed under normal use conditions. In the workplace, wear Nitrile gloves. Disposable nitrile gloves can also be used, but discard after single use.				
Wear work clothing as required by employer code.				
No respiratory protective equipment is required under normal conditions of use. Where the conditions in the workplace require a respirator, it is necessary to follow a respiratory protection program compliance with the standards 29 CFR 1910.134 (OSHA) and ANSI Z88.2. In case of insufficient ventilation or in enclosed area until maximum 10 times of exposure limit, wear half mask respirator with organic vapors cartridges.				
mask respirate	i with organic vapors car	illuges.		
	STEL TWA (8h) TWA (8h) TWA (8h) TWA (8h) Provide sufficie concentrations limits. asures In the workplace wear chemical No protective enditions in the program complinsufficient venions.	TWA (8h) TWA (8h) Inhalable Fraction Mist Mist TWA (8h) Provide sufficient mechanical ventilatio concentrations of vapours, mists, aeros limits. asures In the workplace, wear safety glasses wear chemical splash goggles. No protective equipment is needed unconcentrations of vapours are gloves can all wear work clothing as required by employees. Disposable nitrile gloves can all wear work clothing as required by employees conditions in the workplace require a reprogram compliance with the standards insufficient ventilation or in enclosed ar	STEL 1000 ppm TWA (8h) 1000 ppm TWA (8h) 1000 ppm TWA (8h) Inhalable Fraction Mist Mist TWA (8h) 1 ppm 1 ppm Provide sufficient mechanical ventilation (general or loc concentrations of vapours, mists, aerosols or dust below limits. asures In the workplace, wear safety glasses with side shields wear chemical splash goggles. No protective equipment is needed under normal use of gloves. Disposable nitrile gloves can also be used, but wear work clothing as required by employer code. No respiratory protective equipment is required under normal conditions in the workplace require a respirator, it is need program compliance with the standards 29 CFR 1910.1 insufficient ventilation or in enclosed area until maximum	STEL 1000 ppm 1880 mg/m³ 1000 ppm 1900 mg/m³ 1000 ppm 1900 mg/m³ 1000 ppm 1900 mg/m³ TWA (8h) Inhalable Fraction 5 mg/m³ Mist 10 mg/m³ Mist 15 mg/m³ TWA (8h) Inhalable Fraction 5 mg/m³ Mist 15 mg/m³ TWA (8h) 1 ppm 1.4 mg/m³ Provide sufficient mechanical ventilation (general or local exhaust) to kee concentrations of vapours, mists, aerosols or dust below their respective limits. Basures In the workplace, wear safety glasses with side shields. If there is a risk of wear chemical splash goggles. No protective equipment is needed under normal use conditions. In the workplace of the program of the program of the program of the workplace required by employer code. No respiratory protective equipment is required under normal conditions of conditions in the workplace require a respirator, it is necessary to follow a program compliance with the standards 29 CFR 1910.134 (OSHA) and A insufficient ventilation or in enclosed area until maximum 10 times of experiments.

9. Physical and chemical properties				
Physical state	Viscous liquid	Flammability	Flammable.	
Colour	Translucent	Flammability limits	3.3 to 19%	
Odour	Slight alcohol odor	Flash point	15 to 17°C (59 to 62.6°F)	
Odour threshold	N/Av.	Auto-ignition temperature	363°C (685.4°F)	
рH	6 to 7	Sensibility to electrostatic charges	Yes	
Melting point	<0°C (32°F)	Sensibility to sparks and/or friction	No	
Freezing point	<0°C (32°F)	Vapour density	>1 (Air = 1)	

Boiling point	78 to 78.5°0	C (172.4 to 173.3°F)	Relative density	0.84 to 0.85 kg/L (Water = 1)
Solubility	Soluble in v	vater.	Partition coefficient n-octanol/water	N/Av.
Evaporation rate	N/Av.		Decomposition temperature	N/Av.
Vapour pressure	<6kPa (45 r	mm Hg) @ 20°C (68°F)	Viscosity	N/Av.
Percent Volatile	>99%		Molecular mass	N/Ap.
VOC content	80% (w/w)			
N/	'Av.: Not Available	N/Ap.: Not Applicable	Und.: Undetermined	N/E: Not Established

10. Stability and reactivity			
Reactivity	No reactivity expected.		
Chemical stability	Stable under recommended storage conditions.		
Possibility of hazardous reactions (including polymerizations)	A dangerous reaction will not occur.		
Conditions to avoid	Avoid heat, flame and sparks. Avoid contact with incompatible materials.		
	Strong oxidizing agents (e.g. chlorine, fluorine, nitric acid, perchloric acid, peroxides, nitrates, chlorates, chromates, permanganates and perchlorates).		
Hazardous decomposition products	No decomposition product.		

11. Toxicolo	ogical informa	tion			
Numerical measures of toxicity	Ethyl alcohol	-	7060 mg/kg 39 mg/l/4h 20000 mg/kg	Rat Mouse Rabbit	
	Glycerol	Ingestion	>11500 mg/kg	Rat	LD50
		Inhalation	>0.57 mg/l/1h	Rat	LC50
		Skin	>18500 mg/kg	Rabbit	LD50
	Hydrogen peroxide	Ingestion	1600 mg/kg	Rat	LD50
			>400 mg/kg	Rat	LD50
		Inhalation	· ·	Rat	LC50
		Skin	4060 mg/kg	Rat	LD50
Likely routes of exposure	Skin, eyes, inhalatio	n, ingestio	n.		
Delayed, immediate and chronic effects	Eye contact				skin irritation. Ethanol (CAS no 64-17-5) is (Rabbit, OECD 405).
on one one	Skin contact	Rabbit (C		sts perfo	ure may cause dry skin. Skin Irritation/Corrosion, ormed with each ingredient (>1%) of this mixture
	Inhalation	slight irrit headach	ation of the res	piratory	rapidly absorbed by respiratory tract. May cause system. Prolonged exposure may cause a. The severity of symptoms may vary depending
	Ingestion	followed by heada	by a depressio	n of the	use euphoria, sensations of drunkenness central nervous system which can be manifested ss, incoordination, blurred speech, mental
	Respiratory or skin sensitization		nts present at le espiratory sensi		eater than or equal to 0.1% of this product are not
	IARC/NTP Classification	No ingre	dients listed.		
	Carcinogenicity				eater than or equal to 0.1% of this product are not ACGIH, NIOSH, NTP or OSHA. Ethanol when

		not consumed in an alcoholic beverage is not classifiable as a human carcinogen.	
	Mutagenicity	Ingredients in this product present at levels greater than or equal to 0.1% are not known to cause mutagenic effects.	
	Reproductive toxicity	Ingredients in this product present at levels greater than or equal to 0.1% are not known to cause reproduction effects. The effects of ethanol on reproduction during pregnancy resulting from the consumption of alcoholic beverages were not considered in this assessment.	
	Specific target organ toxicity - single exposure	No target organ is listed.	
	Specific target organ toxicity - repeated exposure	No target organ is listed.	
Interactive effects	No information available.		
Other information	No additional information.		

12. Ecolog	ical information						
Ecological toxicity	Fish - Pimephales promelas [flow-through] LC50 13400 mg/L; 96 h (CAS no 64-17-5) Aquatic Invertebrate - Daphnia magna EC50 9268 mg/L; 48 h (CAS no 64-17-5) Aquatic Plant - Algea, Chlorella vulgaris EC50 275 mg/L; 72 h (CAS no 64-17-5)						
	Fish - Oncorhynchus mykiss - Rainbow trout LC50 54000 mg/L; 96 h (CAS no 56-81-5) Aquatic Invertebrate - Daphnia magna						
Persistence	Not persistent in environment.						
Degradability	The product is a mixture whose ingredients are readily biodegradable (> 60% in 28 days).						
	The product is a mixture of which all ingredients have a low bioaccumulation potential (Log Kow of <3 and / or BCF <500).						
Mobility in soil	The product is a mixture of which some ingredients evaporate very easily from the surface of the soil. Moreover, ingredients have very high mobility in soil.						
Other adverse effects	This chemical does not deplete the ozone layer.						

13. Disposal considerations

Container



Important! Prevent waste generation. Use in full. Organic solvents and wastes residues can be reprocessed (recycle) where there is a recovery program. Observe all federal, state/provincial and municipal regulations. If necessary consult the Department of Environment or the relevant authorities.

14. Transport information						
UN Number	UN 1993					
UN Proper Shipping Name	FLAMMABLE LIQUID, N.O.S. (ethanol)					
Environmental hazards	This material does not contain marine pollutant.					
Special precautions for user	Permit required for transportation with proper DANGER placards displayed on vehicle.					
TDG - Transportation of Dangerous Goods (Canada & US DOT)						

Transport hazard class (es) Packing group Emergency response guidebook 2016 IMO/IMDG - International Maritime Transport Classification UN 1993. FLAMMABLE LIQUID, N.O.S. (ethanol). Class 3, PG II. Emergency schedules (EmS-No) F-E, S-E IATA - International Air Transport Association Classification UN 1993. FLAMMABLE LIQUID, N.O.S. (ethanol). Class 3, PG II. These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and

15. Regulatory inform	ation				
CANADA					
Common name	CAS	CEPA	DSL	NDSL	NPRI
Ethyd alaahal	C4 47 F	V	V		V

regulations, including proper transportation classification and packaging. In addition, if a domestic exemption exists, it is the responsibility of the shipper to define

•••••••	0.10	V = 1.71		11202	
Ethyl alcohol	64-17-5	X	Х		X
Glycerol	56-81-5		Х		
Hydrogen peroxide	7722-84-1	X	Х		

- CEPA: List of Toxic Substances Managed Under Canadian Environmental Protection Act
- DSL: Domestic Substances List Inventory
- NDSL: Non-Domestic Substances List Inventory
- NPRI: National Pollutant Release Inventory Substances

UNITED STATE OF AMERICA

the application of it.

Common name	CAS	TSCA	CER CLA	EPCRA 313	EPCRA 302/304	CAA 112(b) HON	CAA 112(b) HAP	CAA 112(r)	CWA 311	CWA Prio.
Ethyl alcohol	64-17-5	X								
Glycerol	56-81-5	X				Х				
Hydrogen peroxide	7722- 84-1	Х								

- TSCA: Toxic Substance Control Act
- CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act list of hazardous substances
- EPCRA 313: Emergency Planning and Community Right-to-Know Act, Section 313 Toxic Chemicals
- EPCRA 302/304: Emergency Planning and Community Right-to-Know Act, Section 302/304 Extremely Hazardous Substances
- CAA 112(b) HON: Clean Air Act Hazardous Organic National Emission Standard for Hazardous Air Pollutant
- CAA 112(b) HAP: Clean Air Act Hazardous Air Pollutants lists pollutants
- CAA 112(r): Clean Air Act Regulated Chemicals for Accidental Release Prevention

- CWA 311: Clean Water Act - List of Hazardous Substances
- CWA Priority: Clean Water Act - Priority Pollutant list

California Proposition 65

No ingredients listed.

Other regulations

HMIS

HEALTH

FLAMMABILITY

REACTIVITY

PERSONAL PROTECTION

Date (YYYY- MM-DD)	Walter Surface Technologies Inc. 2020-05-20
/ersion	01
Other nformation	REFERENCES: - Haz-Map, Information on Hazardous Chemicals and Occupational Diseases, https://haz-map.com/ - NIOSH Pocket Guide to Chemical Hazards, Centers for Disease Control and Prevention, NIOSH Publications, 2007, http://www.cdc.gov/niosh/npg/npg.html - The National Center for Biotechnology Information, National Institutes of Health (NIH), U.S. National Library of Medicine, https://pubchem.ncbi.nlm.nih.gov/
	ACGIH: American Conference of Governmental Industrial Hygienists AIHA: American Industrial Hygiene Association HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association OSHA: Occupational Safety and Health Administration (USA) NIOSH: National Institute for Occupational Safety and Health NTP: National Toxicology Program RSST: Règlement sur la santé et la sécurité du travail (Québec) GHS: Globally Harmonized System IARC: International Agency for Research on Cancer IDLH: Immediately Dangerous to Life or Health STEL: Short Term Exposure Limit (15 min) TWA: Time Weighted Averages WHMIS: Workplace Hazardous Materials Information System
	To the best of our knowledge, the information contained herein is accurate. However, neither Prī¿½ventis System nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of ar material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.